

## **DECLARATION OF PERFORMANCE (DOP)**

## Product name RÖFIX KHP BASIS

No of the declaration and unique identification code of the product type **247601** 

**Product type Plaster with organic binders** 

Intended use

Organic binding agent containing finishing plastering used for external walls, pillars, partitions and ceilings.

Manufacturer

RÖFIX AG • Badstrasse 23 • A-6832 Röthis • RÖFIX EOOD • 10 Spartak Str • 4490 Septemvri, Bulgaria

System/s of AVCP: System 4

Notified body/ies:
Wien Zert (MA 39),
Rinnböckstraße 5,
1110 Wien
1139

## Declared performance

Important features	Performance	Harmonised technical specification
Water-vapour permeability	V2 middle	EN 15824
Water absorption	W <sub>3</sub> low	
Adhesion strength	≥ 0,3 MPa	
Durability (with regard to frost resistance)	Water permeability coefficient according to EN 1062-3 $\leq$ 0.5 kg / (m <sup>2</sup> · h0.5)	
Thermal conductivity $\lambda_D$	NPD	
Reaction to fire	B - s1, d0 (used on mineral surfaces)	
Dangerous substances	NPD	



The performance of the product identified in this statement is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer named in the declaration.

Eng. Krassimir Christov, Managing Di	rector
--------------------------------------	--------

(Name and function)

"PLOGUKC" EOOD TP. CentreMepu y. "Cnaptak" Ne10 Ten.: 034/405900 фakc: 034/405909 e-mail: office.saptemvri@roofix.com

Septemvri, Bulgaria, 2020-01-07

(Place and date of issue)

(Signature)