



DECLARATION OF PERFORMANCE (DOP)

Product name

RÖFIX W50

No of the declaration and unique identification code of the product type

2291

Product type

Standard mortar for plastering GP

Intended use

Standard plastering mortar GP for indoors and outdoors

Manufacturer

RÖFIX AG • Badstrasse 23 • A-6832 Röthis •
RÖFIX EOOD • 10 Spartak Str • 4490 Septemvri, Bulgaria

System/s of AVCP:

System 4

Notified body/ies:

Wien Zert (MA 39),
Rinnböckstraße 5,
1110 Wien
1139

performed the initial inspection of the manufacturing plant and of factory production control
issued the certificates of conformity of the factory production control
and carries on with continuous surveillance, assessment and evaluation of factory production control according to system 2+.

Component of the thermal insulation systems:
DOP 7071: RÖFIX W50 Thermal insulation system with EPS

Declared performance

Important features	Performance	Harmonised technical specification
Reaction to fire	A2-s1-d0	EN 998-1
Water absorption	W2	
Water vapour permeability	15/35 (Table value)	
Adhesion strength	≥ 0,08 N/mm ² with A, B or C demolition type	
Thermal conductivity	$\lambda_{10,dry,mat} \leq 0,61 \text{ W/(m} \cdot \text{K)}$ P=50% $\lambda_{10,dry,mat} \leq 0,66 \text{ W/(m} \cdot \text{K)}$ P=90% (tab. mean value)	
Durability	NPD	
Dangerous substances	NPD	



The performance of the product identified in this statement is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer named in the declaration.

Signed for and on behalf of the manufacturer by:

Name and function

Röthis, 2021-02-02

Place and date of issue

This document was produced electronically and is valid without signature.

Signature